




























Broadband CPE








Broadband CPE product portfolio

	DSL		
	AX	AC	N
IAD	 DX5401-B0 AX6000	 VMG8825-T50K AC2400	
	 DX3301-T0 AX1800	 VMG8623-T50B AC1200	
Gateway	 DX3300-T0 AX1800	 VMG3927-T50K AC2400	
		 VMG3625-T50B AC1200	
Bridge			 VMG4005-B50A VMG4005-B60A











	Ethernet		
	AX	AC	
IAD	 EX5501-B0 AX6000	 EX5401-B0 AX6000	 EMG5723-T50K AC2400
		 EX3301-T0 AX1800	 EMG5523-T50B AC1200
Gateway	 EX3300-T0 AX1800		 EMG3525-T50B AC1200
WiFi Extender	 WX3401-B0 AX5400	 WX3100-T0 AX1800	 WAP6807 AC2100











Broadband CPE key features

Category	Model	Key features
DSL IAD	DX5401-B0  	<ul style="list-style-type: none"> • VDSL2 supports super vectoring up to profile 35b • WiFi 6 (11ax) 4x4+4x4 for superior performance and coverage • Zyxel MPro Mesh® Solutions (compliant with EasyMesh standards)* • Remote management via TR-069 and TR-181 i2 • Zyxel-developed OPAL for superior flexibility and faster time to market • SFP cage enables Gigabit active fiber (P2P) and GPON (P2M) deployments • VoIP SIP protocol with 3-way conference calls • Multiple SSIDs for various service deployment scenarios • Comprehensive QoS for enhanced triple-play experience
	DX3301-T0  	<ul style="list-style-type: none"> • VDSL2 supports super vectoring up to profile 35b • WiFi 6 (11ax) 2x2+2x2 for superior performance and coverage • Zyxel MPro Mesh® Solutions (compliant with EasyMesh standards)* • Remote management via TR-069 and TR-181 i2 • Zyxel-developed OPAL for superior flexibility and faster time-to-market • VoIP SIP protocol with 3-way conference calls • Multiple SSIDs for various service deployment scenarios • Comprehensive QoS enhanced triple-play experience • Ecofriendly compact design for lower carbon emission
	VMG8825-T50K  	<ul style="list-style-type: none"> • VDSL2 supports super vectoring up to profile 35b • Zyxel MPro Mesh® Solutions (compliant with EasyMesh standards)* • Remote management via TR-069 and TR-181 i2 • NAT, firewall with SPI and DoS for better security • Zyxel-developed OPAL for superior flexibility and faster time-to-market • VoIP SIP protocol with 3-way conference calls • Multiple SSIDs for various service deployment scenarios • Comprehensive QoS enhanced triple-play experience
	VMG8623-T50B  	<ul style="list-style-type: none"> • VDSL2 supports super vectoring up to profile 35b • Zyxel MPro Mesh® Solutions (compliant with EasyMesh standards) • Remote management via TR-069 and TR-181 i2 • NAT firewall with SPI and DoS for enhanced security • Zyxel-developed OPAL for superior flexibility and faster time to market • VoIP SIP protocol with 3-way conference calls • Multiple SSIDs for various service deployment scenarios • Comprehensive QoS for enhanced triple-play experience • Ecofriendly compact design for lower carbon emission

Category	Model	Key features
DSL Gateway	DX3300-T0  	<ul style="list-style-type: none"> • VDSL2 supports super vectoring up to profile 35b • WiFi 6 (11ax) 2x2+2x2 for superior performance and coverage • Zyxel MPro Mesh® Solutions (compliant with EasyMesh standards)* • Remote management via TR-069 and TR-181 i2 • Zyxel-developed OPAL for superior flexibility and faster time-to-market • Multiple SSIDs for various service deployment scenarios • Comprehensive QoS enhanced triple-play experience • Ecofriendly compact design for lower carbon emission
	VMG3927-T50K  	<ul style="list-style-type: none"> • VDSL2 supports super vectoring up to profile 35b • Zyxel MPro Mesh® Solutions (compliant with EasyMesh standards) • Remote management via TR-069 and TR-181 i2 • NAT, firewall with SPI and DoS for better security • Zyxel-developed OPAL for superior flexibility and faster time-to-market • Multiple SSIDs for various service deployment scenarios • Comprehensive QoS enhanced triple-play experience
	VMG3625-T50B  	<ul style="list-style-type: none"> • VDSL2 supports super vectoring up to profile 35b • Zyxel MPro Mesh® Solutions (compliant with EasyMesh standards) • Remote management via TR-069 and TR-181 i2 • NAT firewall with SPI and DoS for enhanced security • Zyxel-developed OPAL for superior flexibility and faster time to market • Multiple SSIDs for various service deployment scenarios • Comprehensive QoS for enhanced triple-play experience • Ecofriendly compact design for lower carbon emission
Bridge	VMG4005-B50A VMG4005-B60A 	<ul style="list-style-type: none"> • VDSL2 17a bonding technology doubles the speed • VDSL2 supports super vectoring of up to profile 35b • TR-286 standard compliant for Metallic Line Testing (MELT) functionality • Remote management via TR-069 and TR-181 i2 • Zyxel-developed OPAL for superior flexibility and faster time-to-market

Broadband CPE key features

Category	Model	Key features
Ethernet IAD	EX5501-B0 	<ul style="list-style-type: none"> • WiFi 6 (11ax) 4x4+4x4 for superior performance and coverage • Zyxel MPro Mesh® Solution (compliant with EasyMesh standards)* • Zyxel Execution Environment (ZyEE) for Linux Containers • Remote management via TR-069 and TR-181 • Zyxel-developed OPAL for superior flexibility and faster time-to-market • VoIP SIP protocol with 3-way conference calls • Multiple SSIDs for various service deployment scenarios • Comprehensive QoS enhanced triple-play experience • 2.5GbE WAN port for premium fiber-grade service • Four 1GbE and one 2.5GbE LAN ports for optimized bandwidth utilization
		
	EX5401-B0 	<ul style="list-style-type: none"> • WiFi 6 (11ax) 4x4+4x4 for superior performance and coverage • Zyxel MPro Mesh® Solutions (compliant with EasyMesh standards)* • SFP cage enables Gigabit active fiber (P2P) and GPON (P2M) deployments • Remote management via TR-069 and TR-181 i2 • Zyxel-developed OPAL for superior flexibility and faster time-to-market • VoIP SIP protocol with 3-way conference calls • Multiple SSIDs for various service deployment scenarios • Comprehensive QoS enhanced triple-play experience • Eco-friendly compact design for lower carbon emission
		
	EX3301-T0 	<ul style="list-style-type: none"> • WiFi 6 (11ax) 2x2+2x2 for superior performance and coverage • Zyxel MPro Mesh® Solutions (compliant with EasyMesh standards)* • Remote management via TR-069 and TR-181 i2 • Zyxel-developed OPAL for superior flexibility and faster time-to-market • VoIP SIP protocol with 3-way conference calls • Multiple SSIDs for various service deployment scenarios • Comprehensive QoS enhanced triple-play experience • Eco-friendly compact design for lower carbon emission
		
EMG5723-T50K 	<ul style="list-style-type: none"> • Zyxel MPro Mesh® Solutions (compliant with EasyMesh standards)* • Remote management via TR-069, TR-181 i2 • NAT, firewall with SPI and DoS for better security • Zyxel-developed OPAL for superior flexibility and faster time-to-market • VoIP SIP protocol with 3-way conference calls • Multiple SSIDs for various service deployment scenarios • Comprehensive QoS enhanced triple-play experience 	
		
EMG5523-T50B 	<ul style="list-style-type: none"> • Zyxel MPro Mesh® Solutions (compliant with EasyMesh standards) • Remote management via TR-069 and TR-181 i2 • NAT firewall with SPI and DoS for enhanced security • Zyxel-developed OPAL for superior flexibility and faster time to market • Multiple SSIDs for various service deployment scenarios • Comprehensive QoS for enhanced triple-play experience • Ecofriendly compact design for lower carbon emission 	
		

Category	Model	Key features
Ethernet Gateway	EX3300-T0 	<ul style="list-style-type: none"> • WiFi 6 (11ax) 2x2+2x2 for superior performance and coverage • Zyxel MPro Mesh® Solutions (compliant with EasyMesh standards)* • Remote management via TR-069 and TR-181 i2 • Zyxel-developed OPAL for superior flexibility and faster time-to-market • Multiple SSIDs for various service deployment scenarios • Comprehensive QoS enhanced triple-play experience • Ecofriendly compact design for lower carbon emission
		
	EMG3525-T50B 	<ul style="list-style-type: none"> • Zyxel MPro Mesh® Solutions (compliant with EasyMesh standards) • Remote management via TR-069, TR-181 i2 • NAT firewall with SPI and DoS for enhanced security • Zyxel-developed OPAL for superior flexibility and faster time to market • Multiple SSIDs for various service deployment scenarios • Comprehensive QoS for enhanced triple-play experience • Ecofriendly compact design for lower carbon emission
		
WiFi Extender	WX3401-B0 	<ul style="list-style-type: none"> • WiFi 6 (11ax) for superior performance and coverage • Zyxel MPro Mesh® Solutions (compliant with EasyMesh standards)* • Remote management via TR-069, TR-098 and TR-181 • Zyxel-developed OPAL for superior flexibility and faster time-to-market • Multiple SSIDs for various service deployment scenarios • Comprehensive QoS enhanced triple-play experience
		
	WX3100-T0 	<ul style="list-style-type: none"> • WiFi 6 (11ax) for superior performance and coverage • Zyxel MPro Mesh® Solutions (compliant with EasyMesh standards)* • Comprehensive QoS enhanced triple-play experience • Remote management via TR-069, TR-098 and TR-181 • Zyxel-developed OPAL for superior flexibility and faster time-to-market • Multiple SSIDs for various service deployment scenarios
		
	WAP6807 	<ul style="list-style-type: none"> • Zyxel MPro Mesh® Solution (compliant with EasyMesh standards)* • 2100 Mbps dual-band concurrent wireless access point • Integrated beamforming technology • Remote management via TR-069 and TR-098 • AP/repeater mode switch
		

* Combining specific Gateway or IAD with the specific Wireless Extender is advised for the ideal mesh network performance. Please refer to the feature matrix in P.8-P.15 for detailed compatibility and availability.

Broadband CPE feature matrix

DSL IAD

Model	11AX		11AC	
	DX5401-B0	DX3301-T0	VMG8825-T50K	VMG8623-T50B
Product name	Dual-Band Wireless AX6000 VDSL2 Gigabit IAD	Dual-Band Wireless AX1800 VDSL2 Gigabit IAD	Dual-Band Wireless AC2400 VDSL2 Gigabit IAD	Dual-Band Wireless AC1200 VDSL2 Gigabit IAD
Hardware				
WAN interface	DSL RJ-11/RJ45/GbE/SFP	DSL RJ-11/RJ-45/GbE	DSL RJ-11/RJ45/GbE	DSL RJ-11/RJ-45/GbE
Ethernet port (10/100/1000)	5 (1 for Ethernet WAN)	5 (1 for Ethernet WAN)	5 (1 for Ethernet WAN)	5 (1 for Ethernet WAN)
POTS FXS port	2	2	2	2
USB port	1 (USB 3.0)	1 (USB 2.0)	2 (USB 3.0/2.0)	1 (USB 2.0)
Voice				
SIP v2 (RFC 3261)	Yes	Yes	Yes	Yes
SDP (RFC 2327)	Yes	Yes	Yes	Yes
RTP (RFC 1889)	Yes	Yes	Yes	Yes
RTCP (RFC 1890)	Yes	Yes	Yes	Yes
G.168 echo cancellation	Yes	Yes	Yes	Yes
VAD/CNG	Yes	Yes	Yes	Yes
CODEC	G.711 a/u law/G.726/G.722/G.729	G.711 a/u law/G.726/G.722/G.729	G.711 a/u law/G.726/G.722/G.729	G.711 a/u law/G.726/G.722/G.729
DTMF detection	Yes	Yes	Yes	Yes
DTMF: In-band and out-of-band	Yes	Yes	Yes	Yes
QoS (IP bandwidth management)	Yes	Yes	Yes	Yes
ToS support	Yes	Yes	Yes	Yes
FAX, modem detection and pass-through	Yes	Yes	Yes	Yes
T.38 FAX	Yes	Yes	Yes	Yes
IVR	Yes	Yes	Yes	Yes
Three way conference	Yes	Yes	Yes	Yes
DSL compliance				
Standards/Profile	VDSL2 Vectoring (up to 35b)/ADSL2+	VDSL2 Vectoring (up to 35b)/ADSL2+	VDSL2 Vectoring (up to 35b)/ADSL2+	VDSL2 Vectoring (up to 35b)/ADSL2+
Wireless				
WLAN	2.4 GHz 4x4 ax + 5 GHz 4x4 ax	2.4 GHz 2x2 ax + 5 GHz 2x2 ax	2.4 GHz 3x3 n + 5 GHz 4x4 ac	2.4 GHz 2x2 n + 5 GHz 2x2 ac
MPro Mesh®				
Compatibility	WX3401-B0	WX3100-T0	WAP6807	-
Availability	Q4/2021	Q4/2021	Q1/2022	Available
Firewall				
Stateful packet inspection	Yes	Yes	Yes	Yes
Denial of service	Yes	Yes	Yes	Yes
VPN				
IPSec (Pass thru)	Yes	Yes	Yes	Yes
Network				
TCP/IP	Yes	Yes	Yes	Yes
PPPoE	Yes	Yes	Yes	Yes
DHCP client/server/relay	Yes	Yes	Yes	Yes
PPPoA	Yes	Yes	Yes	Yes
DHCP server	Yes	Yes	Yes	Yes
UPnP	Yes	Yes	Yes	Yes
IP policy routing	Yes	Yes	Yes	Yes
Multi-to-multi NAT	Yes	Yes	Yes	Yes
Dynamic DNS (DDNS)	Yes	Yes	Yes	Yes
IGMP	Yes	Yes	Yes	Yes
Management				
Web configurator	Yes	Yes	Yes	Yes
TR-069/TR-181 i2	Yes	Yes	Yes	Yes
Remote firmware upgrade	Yes	Yes	Yes	Yes
SNMP	Yes	Yes	Yes	Yes
Physical specifications				
Dimensions (WxDxH)(mm/in.)	258 x 32 x 180/10.15 x 1.25 x 7.08	220 x 35 x 153/8.66 x 1.38 x 6.02	220 x 75 x 200/8.66 x 2.95 x 7.87	220 x 35 x 153/8.66 x 1.38 x 6.02
Weight (g/lb.)	521.8/1.15	387/0.85	549/1.21	325/0.72

Broadband CPE feature matrix

DSL Gateway

Model	11AX DX3300-T0	11AC VMG3927-T50K	VMG3625-T50B	Bridge VMG4005-B50A/VMG4005-B60A
Product name	Dual-Band Wireless AX1800 VDSL2 Gigabit Gateway	Dual-Band Wireless AC2400 VDSL2 Gigabit Gateway	Dual-Band Wireless AC1200 VDSL2 Gigabit Gateway	VDSL2 17a Bonding and 35b Single Line Bridge
Hardware				
WAN interface	DSL RJ-11/RJ-45/GbE	DSL RJ-11/RJ-45/GbE	DSL RJ-11/RJ-45/GbE	DSL RJ-14 or 45
Ethernet port (10/100)	-	-	-	-
Ethernet port (10/100/1000)	5 (1 for Ethernet WAN)	5 (1 for Ethernet WAN)	5 (1 for Ethernet WAN)	1
USB port	1 (USB2.0)	1 (USB 3.0)	1	-
DSL compliance				
Standards/Profile	VDSL2 Vectoring (up to 35b)/ADSL2+	VDSL2 Vectoring (up to 35b)/ADSL2+	VDSL2 Vectoring (up to 35b)/ADSL2+	VDSL2 Vectoring (up to 35b)/ADSL2+
Wireless				
WLAN	2.4 GHz 2x2 ax + 5 GHz 2x2 ax	2.4 GHz 3x3 n + 5 GHz 4x4 ac	2.4 GHz 2x2 n + 5 GHz 2x2 ac	-
MPro Mesh®				
Compatibility	WX3100-T0	WAP6807	-	-
Availability	Q4/2021	Q1/2022	Available	-
Firewall				
Stateful packet inspection	Yes	Yes	Yes	Yes
Denial of service	Yes	Yes	Yes	Yes
VPN				
IPSec (Pass thru)	Yes	Yes	Yes	Yes
Network				
TCP/IP	Yes	Yes	Yes	Yes
PPPoE	Yes	Yes	Yes	Yes
DHCP client	Yes	Yes	Yes	Yes
PPPoA	Yes	Yes	Yes	Yes
DHCP server	Yes	Yes	Yes	Yes
UPnP	Yes	Yes	Yes	Yes
IP policy routing	Yes	Yes	Yes	Yes
Multi-to-Multi NAT	Yes	Yes	Yes	Yes
Dynamic DNS (DDNS)	Yes	Yes	Yes	Yes
IGMP	Yes	Yes	Yes	Yes
Management				
Web configurator	Yes	Yes	Yes	Yes
TR-069/TR-181 i2	Yes	Yes	Yes	Yes
Remote firmware upgrade	Yes	Yes	Yes	Yes
SNMP	Yes	Yes	Yes	Yes
Physical specifications				
Dimensions (WxDxH)(mm/in.)	220 x 35 x 153/8.66 x 1.38 x 6.02	220 x 75 x 200/8.66 x 2.95 x 7.87	220 x 35 x 153/8.66 x 1.38 x 6.02	130 x 32 x 120/5.11 x 1.25 x 4.72
Weight (g/lb.)	383/0.84	549/1.21	325/0.72	173/0.38

Broadband CPE feature matrix

Ethernet IAD

Model	11AX		11AX	11AC	
	EX5501-B0	EX5401-B0	EX3301-T0	EMG5723-T50K	EMG5523-T50B
Product name	Dual-Band Wireless AX6000 Gigabit Ethernet IAD	Dual-Band Wireless AX6000 Gigabit Ethernet IAD	Dual-Band Wireless AX1800 Gigabit Ethernet IAD	Dual-Band Wireless AC2400 Gigabit Ethernet IAD	Dual-Band Wireless AC1200 Gigabit Ethernet IAD
Hardware					
WAN interface	RJ45/GbE	RJ45/GbE/SFP	RJ45/GbE	RJ45/GbE	RJ45/GbE
Ethernet port (10/100/1000)	6 (1 for 2.5GbE WAN)	5 (1 for Ethernet WAN)	5 (1 for Ethernet WAN)	5 (1 for Ethernet WAN)	5 (1 for Ethernet WAN)
POTS FXS port	2	2	2	2	2
USB port	1 (USB 3.0)	1 (USB 3.0)	1 (USB 2.0)	1 (USB 3.0)	1 (USB 2.0)
Voice					
SIP v2 (RFC 3261)	Yes	Yes	Yes	Yes	Yes
SDP (RFC 2327)	Yes	Yes	Yes	Yes	Yes
RTP (RFC 1889)	Yes	Yes	Yes	Yes	Yes
RTCP (RFC 1890)	Yes	Yes	Yes	Yes	Yes
G.168 echo cancellation	Yes	Yes	Yes	Yes	Yes
VAD/CNG	Yes	Yes	Yes	Yes	Yes
CODEC	G.711 a/u law/G.726/G.722/G.729	G.711 a/u law/G.726/G.722/G.729	G.711 a/u law/G.726/G.722/G.729	G.711 a/u law/G.726/G.722/G.729	G.711 a/u law/G.726/G.722/G.729
DTMF detection	Yes	Yes	Yes	Yes	Yes
DTMF: In-band and out-of-band	Yes	Yes	Yes	Yes	Yes
QoS (IP bandwidth management)	Yes	Yes	Yes	Yes	Yes
ToS support	Yes	Yes	Yes	Yes	Yes
FAX, modem detection and pass-through	Yes	Yes	Yes	Yes	Yes
T.38 FAX	Yes	Yes	Yes	Yes	Yes
IVR	Yes	Yes	Yes	Yes	Yes
Three way conference	Yes	Yes	Yes	Yes	Yes
Wireless					
WLAN	2.4 GHz 4x4 ax + 5 GHz 4x4 ax	2.4 GHz 4x4 ax + 5 GHz 4x4 ax	2.4 GHz 2x2 ax + 5 GHz 2x2 ax	2.4 GHz 3x3 n + 5 GHz 4x4 ac	2.4 GHz 2x2 n + 5 GHz 2x2 ac
MPro Mesh®					
Compatibility	WX3401-B0	WX3401-B0	WX3100-T0	WAP6807	-
Availability	Q4/2021	Q4/2021	Q4/2021	Q1/2022	Available
Firewall					
Stateful packet inspection	Yes	Yes	Yes	Yes	Yes
Denial of service	Yes	Yes	Yes	Yes	Yes
VPN					
IPSec (Pass thru)	Yes	Yes	Yes	Yes	Yes
Network					
TCP/IP	Yes	Yes	Yes	Yes	Yes
PPPoE	Yes	Yes	Yes	Yes	Yes
DHCP client/server/relay	Yes	Yes	Yes	Yes	Yes
PPPoA	Yes	Yes	Yes	Yes	Yes
DHCP server	Yes	Yes	Yes	Yes	Yes
UPnP	Yes	Yes	Yes	Yes	Yes
IP policy routing	Yes	Yes	Yes	Yes	Yes
Multi-to-multi NAT	Yes	Yes	Yes	Yes	Yes
Dynamic DNS (DDNS)	Yes	Yes	Yes	Yes	Yes
IGMP	Yes	Yes	Yes	Yes	Yes
Management					
Web configurator	Yes	Yes	Yes	Yes	Yes
TR-069/TR-181 i2	Yes	Yes	Yes	Yes	Yes
Remote firmware upgrade	Yes	Yes	Yes	Yes	Yes
SNMP	Yes	Yes	Yes	Yes	Yes
Physical specifications					
Dimensions (WxDxH) (mm/in.)	250 x 32 x 187/9.84 x 1.26 x 7.36	258 x 32 x 180/10.15 x 1.25 x 7.08	220 x 35 x 153/8.66 x 1.38 x 6.02	220 x 75 x 200/8.66 x 2.95 x 7.87	220 x 35 x 153/8.66 x 1.38 x 6.02
Weight (g/lb.)	473/1.045	521.8/1.15	377/0.83	549/1.21	325/0.72

Broadband CPE feature matrix

Ethernet Gateway

Model	11AX	11AC
	EX3300-T0	EMG3525-T50B
Product name	Dual-Band Wireless AX1800 Gigabit Ethernet Gateway	Dual-Band Wireless AC1200 Gigabit Ethernet Gateway
Hardware		
WAN interface	RJ45/GbE	RJ45/GbE
Ethernet port (10/100/1000)	5 (1 for Ethernet WAN)	5 (1 for Ethernet WAN)
PSTN lifeline port	-	-
USB port	1 (USB 2.0)	1 (USB 2.0)
Wireless		
WLAN	2.4 GHz 2x2 ax + 5 GHz 2x2 ax	2.4 GHz 2x2 n + 5 GHz 2x2 ac
MPro Mesh®		
Compatibility	WX3100-T0	-
Availability	Q4/2021	Available
Firewall		
Stateful packet inspection	Yes	Yes
Denial of service	Yes	Yes
VPN		
IPSec (Pass thru)	Yes	Yes
Network		
TCP/IP	Yes	Yes
PPPoE	Yes	Yes
DHCP client/server/relay	Yes	Yes
PPPoA	Yes	Yes
DHCP server	Yes	Yes
UPnP	Yes	Yes
IP policy routing	Yes	Yes
Multi-to-multi NAT	Yes	Yes
Dynamic DNS (DDNS)	Yes	Yes
IGMP	Yes	Yes
Management		
Web configurator	Yes	Yes
TR-069/TR-181 i2	Yes	Yes
Remote firmware upgrade	Yes	Yes
SNMP	Yes	Yes
Physical specifications		
Dimensions (WxDxH)(mm/in.)	220 x 35 x 153/8.66 x 1.38 x 6.02	220 x 35 x 153/8.66 x 1.38 x 6.02
Weight (g/lb.)	373/0.82	325/0.72

WiFi Extender

Model	11AX	11AC	
	WX3401-B0	WX3100-T0	WAP6807
Product name	Dual-Band AX5400 Wireless Extender	Dual-Band AX1800 Wireless Extender	Dual-Band AC2100 Gigabit Wireless Extender
Hardware			
Ethernet port (10/100/1000)	2	2	2
Wireless			
WLAN	2.4 GHz 2x2 ax + 5 GHz 4x4 ax	2.4 GHz 2x2 ax + 5 GHz 2x2 ax	2.4 GHz 2x2 n + 5 GHz 4x4 ac
MPro Mesh®			
Compatibility	WX3401-B0	WX3100-T0	WAP6807
Availability	Available	Available	Available
Operation modes			
Access point	Yes	Yes	Yes
Client	-	-	-
Repeater	Yes	Yes	Yes
Management			
Web configurator	Yes	Yes	Yes
TR-069/TR-181 i2/TR-098	Yes	Yes	TR-069/TR-098
Remote firmware upgrade	Yes	Yes	Yes
Physical specifications			
Dimensions (WxDxH)(mm/in.)	165 x 36 x 139/6.49 x 1.41 x 5.47	150 x 39.8 x 158/5.9 x 1.3 x 5.18	165 x 36 x 139/6.49 x 1.41 x 5.47
Weight (g/lb.)	290/0.64	308/0.68	290/0.64

Corporate headquarters

Zyxel Communications Corp.
Tel: +886 3 578 3942
Fax: +886 3 578 2439
Email: sales@zyxel.com.tw
<https://service-provider.zyxel.com>

EMEA

Zyxel Belarus
Tel: +375 25 604 3739

Zyxel Benelux
Tel: +31 23 555 3689
Fax: +31 23 557 8492

Zyxel Bulgaria
Tel: +3592 4443343

Zyxel Czech Republic
Tel: +420 241 091 350
Hotline: +420 241 774 665
Fax: +420 241 091 359

Zyxel Denmark
Tel: +45 39 55 07 00
Fax: +45 39 55 07 07

Zyxel Finland
Tel: +358 9 4780 8400

Zyxel France
Tel: +33 (0) 4 72 52 97 97
Fax: +33 (0) 4 72 52 19 20

Zyxel Germany
Tel: +49 (0) 2405 6909 0
Fax: +49 (0) 2405 6909 99

Zyxel Hungary & SEE
Tel: +36 1 848 0690

Zyxel Iberia
Tel: +34 911 792 100

Zyxel Italy
Tel: +39 011 2308000

Zyxel Kazakhstan
Tel: +7 727 350 5683
Fax: +7 727 2590 689

Zyxel Israel
Email: da.sales@zyxel.com.tw

Zyxel Egypt
Email: da.sales@zyxel.com.tw

Zyxel Norway
Tel: +47 22 80 61 80
Fax: +47 22 80 61 81

Zyxel Poland
Tel: +48 223 338 250
Hotline: +48 226 521 626
Fax: +48 223 338 251

Zyxel Romania
Tel: +40 31 0809 888
Fax: +40 31 0809 890

Zyxel Russia
Tel: +7 499 705 6106

Zyxel Slovakia
Tel: +421 220 861 847
Hotline: +421 220 861 848
Fax: +421 243 193 990

Zyxel Sweden
Tel: +46 8 55 77 60 60
Fax: +46 8 55 77 60 61
Email: isp@zyxel.eu

Zyxel Switzerland
Tel: +41 (0) 44 806 51 00
Fax: +41 (0) 44 806 52 00

Zyxel Turkey
Tel: +90 212 314 18 00
Fax: +90 212 220 25 26

Zyxel UK
Tel: +44 (0) 118 9121 700
Fax: +44 (0) 118 9797 277

Zyxel Ukraine
Tel: +380 89 323 9959

APAC

Zyxel India
Tel: +91 11 4760 8800
Fax: +91 11 4052 3393
Email: info@zyxel.in

Zyxel Malaysia
Email: apac.sales@zyxel.com.tw

Zyxel Philippine
Email: apac.sales@zyxel.com.tw

Zyxel Singapore
Email: apac.sales@zyxel.com.tw

Zyxel Taiwan (Taipei)
Tel: +886 2 2739 9889
Fax: +886 2 8913 1896
Email: sales_tw@zyxel.com.tw

Zyxel Thailand
Tel: +66 (0) 2831 5315
Fax: +66 (0) 2831 5395
Email: info@zyxel.co.th

Zyxel Vietnam
Email: apac.sales@zyxel.com.tw

Zyxel Japan
Email: apac.sales@zyxel.com.tw

Zyxel Australia
Email: apac.sales@zyxel.com.tw

North America

Zyxel USA
Tel: +1 714 632 0882
+1 800 255 4101 (free)
Fax: +1 714 632 0858
Email: keyaccount@zyxel.com

Zyxel Canada
Tel: +1 714 632 0882
+1 800 255 4101 (free)
Fax: +1 714 632 0858
Email: keyaccount@zyxel.com

South America

Zyxel Brazil
Tel: +55 (11) 3373 7470
Fax: +55 (11) 3373 7510
Email: comercial@zyxel.com.br

Zyxel Bolivia
Email: sa.sales@zyxel.com.tw

Zyxel Chile
Email: sa.sales@zyxel.com.tw

Zyxel Colombia
Email: sa.sales@zyxel.com.tw

Zyxel Ecuador
Email: sa.sales@zyxel.com.tw

Zyxel Paraguay
Email: sa.sales@zyxel.com.tw

Zyxel Peru
Email: sa.sales@zyxel.com.tw

Zyxel Uruguay
Email: sa.sales@zyxel.com.tw

Zyxel Argentina
Email: sa.sales@zyxel.com.tw

For more product information, visit us on the web at
<https://service-provider.zyxel.com>

Copyright © 2022 Zyxel and/or its affiliates. All rights reserved.
All specifications are subject to change without notice.

